

**GeneralAire® Models GF-DH75 & GF-DH100**  
**Wi-Fi Dehumidifiers**

Wi-Fi & Touch Screen Control

**Spec Sheet**


*Installs Quickly & Easily*

GF-DH75 & GF-DH100		
Capacity	Up To 75 Pints Per 24 Hours @ 80°F / 27°C - 60% RH	Up To 100 Pints Per 24 Hours @ 80°F / 27°C - 60% RH
Weight (Pounds)	58	65
Dimensions (Inches)	12.75 H x 12.6 W x 21 D	15.75 H x 12.6 W x 21 D
Home Size (Square Feet)	3,800	5,200
Control	Wi-Fi and Touch Screen	
Power Supply	120VAC, 60Hz	120VAC, 60Hz
Energy Factor (liters/kwh)	2.0	1.86
Current Draw (Amps)	6.2	8.8
Air Flow (CFM)	180	220
Inlet Air Operating Temperature	50°F - 90°F / 10°C - 32°C	
Control Board Display Temperature	-4°F - 158°F operating / -22°F - 176°F storage -20°C - 70°C operating / -30°C - 80°C storage	
Filter Dimensions (Inches)	MERV 11 Pleated Filter GFI #7143 10 x 12 x 1 Replace Every 6 Months	MERV 11 Pleated Filter GFI #7144 12 x 12 x 1 Replace Every 6 Months
Cabinet Insulation	Foil-faced fiberglass 1/2" thick & closed cell foam	
Duct Connections (Inches)	8 Diameter (Inlet & Outlet)	10 Diameter (Inlet & Outlet)
Drain Pan	Heavy Duty, Injection Molded	
Noise (dB)	Less Than 55 (unducted)	
Warranty (Years)	Five	
Typical Installation	Crawl Space, Attic, Basement; Ducted or Unducted	
In The Box	Dehumidifier, Installation Manual, Power Cord, MERV 11 Filter, Duct Mount Collars	



**Accessories**

- Duct Mount Collars (Included)
- Hanging kits GF-6560
- Dehumidistat GF-DC1



Download the  
 GeneralAire® WiFi APP  
 (Apple APP Store or  
 Google Play)

Our Brands



Last Updated: 06-2021



**Canadian General Filters**  
 Limited

400 Midwest Rd.  
 Toronto, ON M1P 3A9  
 Canada  
 Toll Free: (888) 216-9184  
 www.generalaireiaq.ca  
 sales@GeneralAireIAQ.ca

**GeneralAire® Models GF-DH75 & GF-DH100**  
**Wi-Fi Dehumidifiers**

Wi-Fi & Touch Screen Control

**Spec Sheet**

*Installs Quickly & Easily*

**GF-DH75 & GF-DH100 Features**

- Remove up to 100 pints per day.
- Wi-Fi and touch screen control for user convenience.
- Fan-only Function. Set for 10, 20, or 30 minutes per hour.
- Filter Hour Indicator (replace MERV 11 filter annually).
- Low Temperature Shutoff.
- Comfortable handles integrated into both the box and the unit for ease of installation.
- Small footprint and light weight enhances installation options.
- Adjustable feet for leveling.
- Safety grates.
- Duct mount collars (included).
- Quarter turn screw release for easy MERV 11 filter replacement.



See installation manual for instructions on how to download and use the GeneralAire® APP. Or go to [www.generalfilters.com](http://www.generalfilters.com), dehumidifier help topics.

**New APP Features**

- **NEW!** Help buttons take you to dehumidifier help topics on [www.generalfilters.com](http://www.generalfilters.com).
- **NEW!** Humidity sensor offset (+/- 5%) for calibration to another humidity measuring device in the home.
- **NEW!** Low voltage connection for remote dehumidistat or water leak detection device.
- **NEW!** APP attempts to reconnect should Wi-Fi be lost until connection is restored.
- **NEW!** Dewpoint lockout setpoint.



**Maintenance**

**Maintenance of your new GeneralAire® Dehumidifier is minimal:**

- Replace the MERV 11 pleated filter once every 6 months.
- \*\*Do not operate your dehumidifier without a filter.



GF-7143  
for GF-DH75



GF-7144  
for GF-DH100

**Product Support**

- Installation Manual
- Home Owner Brochure
- [www.GeneralAireIAQ.ca](http://www.GeneralAireIAQ.ca)
- Tech Support (888) 216-9184